

Europäisches Patentamt
European Patent Office
Office européen des brevets



(11) EP 0 491 347 B1

(12) EUROPEAN PATENT SPECIFICATION

(45) Date of publication and mention
of the grant of the patent:
26.02.1997 Bulletin 1997/09

(51) Int. Cl.⁶: A61F 13/62

(21) Application number: 91121581.2

(22) Date of filing: 17.12.1991

(54) Absorbent article

Saugfähiger Artikel

Article absorbant

(84) Designated Contracting States:
BE DE ES FR GB IT NL SE

(30) Priority: 17.12.1990 US 628251

(43) Date of publication of application:
24.06.1992 Bulletin 1992/26

(60) Divisional application: 95114306.4

(73) Proprietor: KIMBERLY-CLARK CORPORATION
Neenah, Wisconsin 54956-0349 (US)

(72) Inventors:
• Siebers Bruce Michael
Appleton, Wisconsin 54915 (US)

• Travis, Gary Lee
Oshkosh, Wisconsin 54901 (US)
• Odorzynski, Thomas Walter
Green Bay, Wisconsin 54301 (US)

(74) Representative: Diehl, Hermann O. Th., Dr. et al
Diehl, Glaeser, Hiltl & Partner
Patentanwälte
Postfach 19 03 65
80603 München (DE)

(56) References cited:
EP-A- 0 233 364 EP-A- 0 278 866
EP-A- 0 338 680 EP-A- 0 374 730
GB-A- 2 074 011 GB-A- 2 233 876
US-A- 4 299 223

EP 0 491 347 B1

Note: Within nine months from the publication of the mention of the grant of the European patent, any person may give notice to the European Patent Office of opposition to the European patent granted. Notice of opposition shall be filed in a written reasoned statement. It shall not be deemed to have been filed until the opposition fee has been paid. (Art. 99(1) European Patent Convention).

Description

The present invention pertains to absorbent articles, especially to diapers, incontinence garments, and the like.

Diapers or incontinence garments generally comprise a liquid-impermeable barrier sheet, a liquid-permeable bodyside liner, and an absorbent medium therebetween. They may generally include some type of attaching system for fitting the diaper or garment to the wearer. The present invention is intended for use with these types of articles, and also with other types of articles that require some type of attaching feature, such as articles being surgical gowns, and other personal care or health care garments.

Mechanical attachments, such as hook-and-loop systems, have been used on garments in the past. However, various limitations have prevented the widespread commercialization of these systems on disposable garments or other disposable articles. The most apparent limitations to the commercialization include the cost of the system and the functionality of that system. Typically, the cost and functionality of the system is a trade-off. In other words, greater functionality and performance can be achieved by using more expensive materials.

For example EP-A-0 374 730 refers to a fastener system for a disposable diaper. The diaper has a first mechanical fastener to close the waistband and a second fastener to enable rolling and folding the garment after use and thereby securing it in a net bundle for disposal. The fasteners disclosed do not present any particular feature of improved performance in order to avoid failures in the hook-and-loop systems.

Generally, hook-and-loop systems fail in the "peel" mode. For example, a peel mode exists when one component is held stationary, while the second component is pulled off the first component sequentially. When two attaching components, such as a plurality of hooks and a plurality of loops, are disengaged in the peel mode, the hooks and loops are progressively separated. That is, each row or line of hooks is disengaged a little at a time until all of the hooks are disengaged from their respective loops. The peel performance of hook-and-loop systems is very sensitive to the cost/performance ratio. Generally, to obtain higher peel, a higher basis weight loop must be used which ultimately translates to more loops, thicker fabric, and greater overall cost.

A "shear" mode failure, in comparison, exists when the two components are being pulled apart by oppositely directed forces lying in the same plane. The shear mode action is a sliding, linear action, in contrast to the peel mode, which is a curvilinear type of motion or action.

A "latching" mode failure exists when the two components are being pulled apart by oppositely directed forces acting generally perpendicular to the plane of the components.

The present invention suggests various features

and techniques to improve the performance of hook-and-loop systems and provides an absorbent article according to independent claim 1. Further advantageous features, aspects and details of the article are evident from the dependent claims, the description and the drawings.

The present invention provides an absorbent article comprising a composite which comprises a substrate and an absorbent on said substrate.

Said composite further comprises oppositely disposed front and back end portions.

The absorbent article further comprises a first releasably engageable member on said back end portion of said composite and a second releasably engageable member associated with said front end portion of said composite.

Said first and said second releasably engageable members are releasably engageable together by means of a hook-and-loop system.

Said absorbent article is characterized in that said first and said second releasably engageable members are elastically disposed with said composite for applying a predetermined tension to said releasably engageable members when engaged.

More specifically the invention provides a disposable diaper, disposable incontinence garment, and the like in which attachment, especially tensioning attachment, is accomplished with an improved mechanical fastening system.

In one embodiment of the present invention there is provided an absorbent article comprising a composite including a substrate, an absorbent, and front and back end portions. A first releasably engageable member is on the back end portion, and a second releasably engageable member is with the front end portion. A buckling mechanism joins the second releasably engageable member to the front end portion.

In another embodiment of the present invention the back end portion has an attaching member, and a foldable trapping panel is on the front end portion. The trapping panel comprises a base panel and a flap panel, and the attaching member is releasably engageable between them.

In yet another embodiment of the present invention a tensioning mechanism applies tension to the first and second releasably engageable members.

The above-mentioned and other features and aspects of this invention, and the manner of attaining them, will become more apparent and the invention itself will be better understood by reference to the following description of the embodiments of the invention taken in conjunction with the accompanying drawings, wherein:

Fig. 1 is a perspective view of the back of a diaper incorporating some principles of the present invention;

Fig. 2 is a perspective front view of the diaper in Fig. 1 partially broken away;

Fig. 3 is a cross-sectional view of Fig. 2 taken along line 3-3 and viewed in the direction of the arrows;

Fig. 4 is a cross-sectional view of Fig. 2 taken along line 4-4 and viewed in the direction of the arrows;

Fig. 5 is a schematic of an apparatus for applying adhesive beads in a spaced-apart fashion upon a material sheet;

Fig. 6 is a plan view of the applied adhesive beads on the material sheet;

Fig. 7 is a graph comparing the closure force of a conventional hook-and-loop system and a hook-and-loop system of the present invention;

Fig. 8 is an enlarged side elevational view illustrating the attachment of a loop material on a substrate in accordance with the present invention;

Fig. 9 is an enlarged side elevational view of the loop material in Fig. 8 in a buckled, tensioned state; Fig. 10 is a perspective view of the back of a diaper incorporating other principles of the present invention;

Fig. 11 is an enlarged side elevational view illustrating the closed position of the attaching system illustrated in Fig. 10; and

Fig. 12 is a graph comparing the closure force of a hook-and-loop system without a trap feature and a hook-and-loop system incorporating a trap feature of the present invention.

Fig. 13A is an enlarged side elevational view illustrating a hook-and-loop system in a conventional untensioned state;

Fig. 13B is an enlarged side elevational view illustrating a hook-and-loop system of the present invention in a tensioned state;

Fig. 14 is a graph illustrating increases in latching forces as tension is increased on the system;

Fig. 15 is a graph comparing improved mechanical fastening for different hook types under varying tensions; and

Fig. 16 is an illustration of equipment used with the described latching test procedure.

Although it is contemplated that the present invention is operable in a baby diaper, child's training pant, adult incontinence products, and other personal or health care products, the present description will be made in terms of a baby diaper for ease of explanation and illustration.

Referring to Figs. 1-4, diaper 2 generally comprises backsheet 4, topsheet 6, and absorbent medium 8 therebetween. Leg elastics 10 are joined to side margins 12 of diaper 2 in order to gather or shirr at least intermediate portion 14 of diaper 2. Diaper 2 further comprises a front waist portion 16, rear waist portion 17, and ear portions 18 that are generally integral with rear waist portion 17. As can be seen in Figs. 1 and 2, intermediate portion 14 has a more narrow width than front and rear waist portions 16, 17, thereby giving diaper 2 a generally hour-glass shape. In Fig. 1, the arrow designated L represents the length dimension of diaper 2 and the

machin direction in the manufacture of diaper 2, and the arrow perpendicular thereto designated as T indicates the width of diaper 2, as well the cross direction of the diaper during the manufacturing process.

Front waist portion 16 includes ear sections 20 which have disposed therebetween loop panel 22, which comprises the loop component of the hook-and-loop system. Loop panel 22 can be a fabric material manufactured to have a raised loop construction in which the fabric is stabilized, i.e., the individual loops are erect from the fabric's base, through a napping treatment. Panel 22 can also be any suitable material having non-woven loops thereon. Loop panel 22 is attached to front waist portion 16 of backsheet 4 such that the loops extend outwardly therefrom. The geometric shape of loop panel 22 can be any desired shape, such as rectangular, irregular, diamond, triangular, circular, oval, chevron, or the like. As illustrated, loop panel 22 is generally rectangular in shape.

Referring to Figs. 1-6, loop panel 22 is bonded or attached to backsheet 4 in a manner that is unique and results in enhanced mechanical attaching, specifically increasing the peel, shear, and latching strengths of the attaching system. Rather than bonding the entire under-surface of loop panel 22 to the surface of backsheet 4, only discrete or predetermined sections of panel 22 are attached or bonded to backsheet 4, thereby leaving portions of loop panel 22 unattached and free to move relative to backsheet 4. By thus controlling the bonding or attaching pattern of loop panel 22, the peel, shear, and latching properties of the hook-and-loop system are significantly enhanced, as graphically illustrated in Fig. 7.

Referring specifically to Figs. 5 and 6, a roll of loop material 24 is unwound from reel 26 and passed below hot melt die 28 that is in fluid communication with hopper 30, which contains a hot melt adhesive. The hot melt adhesive is applied by running loop material 24 under die 28 which applies spaced-apart beads 32 of adhesive onto loop material 24 in the machine direction, as illustrated by the arrow in Fig. 5. Since beads 32 are spaced apart, they naturally form spaces 34 therebetween.

The apparatus in Fig. 5 further includes a cutting device 36 including blade 38, which is reciprocated downwardly to cut a plurality of loop panels 22 from loop material 24.

The adhesive beads 32 range in their width from about 1 millimeter to about 15 millimeters, and the width of each space 34 is generally in the range from about 1 millimeter to about 30 millimeters. In one preferred embodiment, beads 32 are 3 millimeters in width, and are spaced about 3 millimeters apart, i.e., spaces 34 have a width of about 3 millimeters. Loop panel 22 is then attached to backsheet 4 between ear sections 20, as illustrated in Fig. 1.

As illustrated in Figs. 5 and 6, adhesive beads 32 are applied in a parallel, linear fashion, but the present invention contemplates application of adhesive beads 32 in any desired pattern as long as the resulting appli-

cation produces spaced-apart areas of adhesive, such as beads 32.

Referring to Figs. 1-4, 8, 9, each ear portion 18 includes a hook tab 40 extending outwardly thereon and including a plurality of hook members 42 for engaging a plurality of loop members 44. As illustrated in Fig. 3 and Fig. 9, each individual hook member 42 can face a single direction. However, the present invention contemplates that the hook members 22 can be oriented in two or more directions. For example, a first predetermined set of rows of hook members 42 could face inwardly, as illustrated in Fig. 3, while other predetermined remaining rows can have their hook members 42 facing in an opposite direction. Alternatively, individual ones of hook members 42 can be oriented in any different number of directions as required.

Hook members 42 can have any desired geometry or shape, and can be made of any suitable material. Hook members 42 can be made of a nylon material, or of materials represented in Fig. 15 as unidirectional HTH 706, HTH 707, or HTH 708 that can be purchased from Velcro Industries B.V., Amsterdam, Netherlands or affiliates thereof. Shapes of members 42 can be hook-, mushroom-shaped, or any other desired shape. Hook member density on a respective hook tab 40 is generally within the range of about 30 to about 160 hooks per square centimeter, and preferably about 115 hooks per square centimeter. Each hook tab 40 also may have a row density within the range of about 3 to about 30 rows per lineal centimeter of width, and preferably a row density of about 15 rows per lineal centimeter. Naturally, these ranges of hook density and row density can vary and be dependent upon the peel and shear characteristics of the type and geometry of material used.

The present invention contemplates interchanging the position or placement of the hook members and loop members on their particular garment or article.

Referring now to Fig. 8, there is illustrated an enlarged side elevational view of backsheet 4 having attached thereto loop panel 22 and its loop members 44 by the spaced-apart adhesive beads 32. Between beads 32 are spaces 34 in which loop panel 22 is unattached to backsheet 4. Upon engaging a respective hook tab 40 to loop panel 22 such that hook members 42 engage loop members 44, and upon application of a tension as illustrated by the arrow in Fig. 9, loop panel 22 will distort or flex with a plurality of buckles 46. This generally results in an increase in the peel, shear, and/or latching strengths between hook tabs 40 and loop panel 22. As graphically illustrated in Fig. 7, graph line C illustrates the closure force of a conventional hook-and-loop system in which the loop panel is totally adhered to its substrate. In contrast, graph line I illustrates the increase in closure force provided by the present invention in which loop panel 22 is intermittently or discretely attached to its backsheet 4. Without being bound to any specific theory or mechanism, it has been found that the increase in peel, shear, and latching strengths results from intermittent attachment of loop

panel 22 to backsheet 4, thereby forming a plurality of buckles 46 when hook tabs 40 are engaged under tension to loop panel 22. A preferred tension range is between about 19.69 g per cm (about 50 grams per inch) to about 196.9 g per cm (500 grams per inch).

Referring now to Fig. 10, diaper 48 illustrates another embodiment of the present invention. Diaper 48 is identical to diaper 2 except in the following description. Each ear portion 18 has joined thereto hook tab 50 having a plurality of hook members 42 disposed on both inner surface 52 and outer surface 54 of a respective hook tab 50. Generally, hook tab 50 can be made of a stretchable or elastomeric material, or hook tab 50 can be joined to a respective ear portion 18 by an intermediate strip of stretchable or elastic material that joins hook tab 50 to ear portion 18.

Front waist portion 16 of backsheet 4 has disposed thereon two separate loop panels 56, 58. Since loop panels 56, 58 are identical, a description of only loop panel 56 will be made. Loop panel 56 includes loop panel base 60 joined to backsheet 4 and loop panel flap 62 which is hingedly connected to loop panel base 60, as illustrated in Fig. 10. This permits loop panel flap 62 to be folded back and forth between a generally unfolded position, in which it is substantially coplanar with loop panel base 60, and a folded position, in which it is folded over and on top of loop panel base 60 such that their respective loop members 44 are in mutually facing relationship.

Referring to Figs. 10 and 11, upon placing diaper 48 about the wearer, each ear portion 18 is drawn around the waist section of the wearer and a respective hook tab 50 is stretched, i.e., placed under tension, as necessary for a proper fit, and placed against loop panel base 60 to engage hook members 42 on inner surface 52 with loop members 44 of loop panel base 60. Loop panel flap 62 is then folded over and engaged with hook tab 50 such that loop members 44 of loop panel flaps 62 engage hook members 52 on outer surface 54 of hook tab 40. Although Fig. 11 illustrates hook members 52 as having their open or mouth ends oriented in the same direction, hook members 52 may be multiply directed as required to provide the desired attachment.

Referring to Fig. 12, graph line A represents the closure force of a conventional hook-and-loop system without a loop panel flap, and graph line P illustrates the present invention in which loop panel flap 62 and loop panel base 60 trap hook members 52 of hook tab 50.

Referring to Fig. 13A, a conventional hook-and-loop system in an untensioned state is illustrated. Because of the untensioned state, there is a certain amount of looseness or play between individual hooks and loops that can result in a less than desirable fastening system. In contrast, Fig. 13B illustrates the hook-and-loop system of the present invention in a tensioned state that causes the hooks to be engaged firmly without play with their respective loops. This increases the stability and performance of the fastening system.

For example, Figs. 14 and 15 illustrate the

increase in latching forces for hooks made of different materials as tension is increased. Thus, regardless of the hook material or article with which the fastening system of the present invention may be used, tension enhances the performance of all systems to some degree.

Test Procedures

PEEL TEST PROCEDURE

Peel is determined according to ASTM Designation D1876-72, "Standard Test Methods for Peel Resistance of Adhesives (T-Peel Test)", subject to the following modification: No test panels are used; hook-and-loop materials are directly engaged and are not mounted on any other substrate unless specified. Test direction of the materials should be noted. No panels are used. The engaged test materials are rolled five cycles; where one cycle equals once in each direction. The hook material is clamped into the upper jaw and the loop material is clamped into the lower jaw.

SHEAR TEST PROCEDURE

Shear is determined according to ASTM Designation D3654-82, "Standard Test Method for Holding Power of Pressure-Sensitive Tapes", and which is subject to the following modification: In relation to the test, the closure is placed under an increasing load. The system being tested is a hook-and-loop closure system. The apparatus should include an "INSTRON" or equivalent tensile tester. In carrying out the procedure, test direction of the materials should be noted. The test materials are rolled five cycles (6.45 cm^2 (one square inch)), where one cycle equals once in each direction. The hook material is clamped into the lower jaw of the INSTRON tensile tester. The engaged system (hook-and-loop) is pulled until failure. In doing calculations, the peak load is determined and recorded in grams.

LATCHING TEST PROCEDURE

Latching force is measured by applying a hook material to a loop material, applying a lateral force to the interface between the hook and loop materials, and then separating them with a vertical force. The value of the vertical force necessary to separate the two materials is the peak force or load in grams. This test method indicates the effect of tension, such as that applied by an elastic member, on a hook and loop closure system. In this test the phrase "latching force" means the force required to disengage a hook material from a loop material resulting from a pull perpendicular to the plane of attachment of the materials to which a fixed lateral force is applied. The phrase "lateral force" means the force applied in parallel to the interface of the hook and loop materials, and the phrase "vertical force" means the force applied perpendicular to the interface of the

hook and loop materials.

Referring to figure 16, there is illustrated a suitable tensile testing machine 70 including a suspension line 72 connected to machine 70 and hanging downwardly therefrom. Latching force test fixture 74 is horizontally mounted and is selectively moveable in the horizontal by means of threaded rod 76. Fixture 74 includes a spring 78. Base support 80, which may be a part of tensile testing machine 70, is used to fix a stainless steel test panel 82 in a stationary position. Hook mounting block 84 includes a vertically oriented eye screw 86 connected to suspension line 72 and a horizontally disposed eye screw 88 connected to spring 78.

A hook and loop closure system is tested by mounting the hook material on the undersurface of hook mounting block 84 and mounting a loop material on the top surface of test panel 82, and then utilizing a lateral force applied by fixture 74 and a vertical force applied by machine 70. This test method is used to analyze the effect of tension on a hook and loop closure system particularly when the hooks are oriented in the direction of the applied tension force.

Tensile testing machine 70 can be any suitable machine that can supply a constant rate of extension having a rate of traverse of about 305 millimeters per minute. Test panel 82 preferably has the dimensions of 51 millimeters x 152 millimeters. Hook mounting block 84 should be made of aluminum having a mounting surface with a dimension of about 25 millimeters x 13 millimeters.

The test procedure occurs in generally two stages, one being the preparing of the specimens and the other being the determination of latching force. The preparations of specimens includes cutting a 25 millimeter square specimen of the hook material and attaching it to the hook mounting block 84 with a two-sided adhesive tape that has an adhesive strength greater than the hook and loop closure system being tested. The hook material should be mounted in a manner that will enable any directionality of the hooks to be utilized in the most efficient manner with regard to the tensioning force. The loop material is cut to have the dimensions of about 30 millimeters x 90 millimeters, and then attached to the stainless steel test panel 82 so that there is approximately six millimeters distance between the edge of the loop specimen and the edge of the test panel 82. Again, a two-sided adhesive tape is used to attach the loop material with the tape having a greater adhesive strength than the hook and loop closure system.

The determination of the latching force is accomplished by first inserting an empty test panel 82 in base support 80. An empty hook mounting block 84 is centered in tensile testing machine 70 by means of suspension line 72. Hook mounting block 84 is then positioned to slightly rest on test panel 82 with minimal slack in suspension line 72. The empty test panel is then replaced with a test panel 82 having the loop material attached thereto. Hook mounting block 84, which has the material attached to its undersurface, is then placed

on top of the loop material without applying any pressure. A lateral force is then selectively applied by means of latching force test fixture 74. Thereafter, tensile testing machine 70 is activated to apply a vertical force until the hook and loop materials are separated. The applied force at which the hook and loop materials separate is the peak load for the applied lateral force.

Claims

1. An absorbent article (2), comprising:

a composite comprising a substrate and an absorbent (8) on said substrate,

said composite further comprising oppositely disposed front (16) and back (17) end portions,

a first releasably engageable member (40) on said back end portion (17) of said composite,

a second releasably engageable member (22) associated with said front end portion (16) of said composite,

said first (40) and said second (22) releasably engageable members being releasably engageable together by means of a hook-and-loop system,

said absorbent article being characterized in that:

said first (40) and said second (22) releasably engageable members are elastically disposed with said composite for applying a predetermined tension to said releasably engageable members when engaged.

2. The article of claim 1 wherein said first releasably engageable member comprises a plurality of hook members and said second releasably engageable member comprises a plurality of loop members.

3. The article of claim 1 wherein said first releasably engageable member comprises a plurality of loop members and said second releasably engageable member comprises a plurality of hook members.

4. The article of one of claims 1 to 3 wherein said second releasably engageable member (22) is intermittently joined to said front end portion (16) or said first releasably engageable member (40) is intermittently joined to said back end portion (17) at a plurality of spaced apart lines (32) of joinder.

5. The article of claim 4 wherein said joinder lines (32) are lines of adhesive.

6. The article of claim 4 wherein said joinder lines (32) are lines of sonic bonding.

7. The article of claim 4 wherein said joinder lines (32) are lines of heat sealing.

8. The article of one of claims 4 to 7 wherein each said joinder line (32) has a width of from about 1 millimeter to about 15 millimeters.

9. The article of one of claims 4 to 8 wherein said joinder lines (32) are spaced apart from about 1 millimeter to about 30 millimeters.

10. The article of one of claims 2 to 9 wherein said plurality of hooks are oriented in a single direction.

11. The article of one of claims 2 to 9 wherein said plurality of hooks are multiply oriented.

12. The article of one of claims 2 to 11 wherein said plurality of hooks have a hook density in the range from about 30 hooks per square centimeter to about 160 hooks per square centimeter.

13. The article of one of claims 2 to 12 wherein said plurality of hooks are generally arranged in rows and have a row density in the range of from about 3 rows per lineal centimeter to about 30 rows per lineal centimeter.

14. The article of one of the preceding claims wherein a tension between 19.69 g/cm (50 grams per inch) to 196.99 g/cm (500 grams per inch) is applied between said first (40) and second (22) releasably engageable members when engaged.

15. The article of one of the preceding claims wherein one of said releasably engageable members comprises a stationary base panel (60) and a freely moveable flap panel (62), and said other releasably engageable member is releasably engageable between said stationary base panel (60) and said freely moveable flap panel (62).

16. The article of claim 15 wherein said other engageable member comprises a stretchable material.

Patentansprüche

1. Saugfähiger Artikel (2) mit

einem ein Substrat und ein darauf angeordnetes Absorbens (8) aufweisender Verbundstoff,

wobei der Verbundstoff des weiteren gegenüberliegende vordere (16) und hintere (17) Endabschnitte aufweist,

einem ersten auf dem hinteren Endabschnitt (17) des Verbundstoffes vorgesehenen, lösbar verbindbaren Element (40),

einem zweiten dem vorderen Endabschnitt (16) des Verbundstoffes zugeordneten, lösbar verbindbaren Element (22),

wobei das erste lösbar verbindbare Element (40) und das zweite lösbar verbindbare Element (22) miteinander mittels eines Haken- und Ösensystems lösbar verbindbar sind,

wobei der saugfähige Artikel dadurch gekennzeichnet ist, daß

das erste lösbar verbindbare Element (40) und das zweite lösbar verbindbare Element (22) elastisch mit dem Verbundstoff angeordnet sind, um eine vorbestimmte Spannung auf die lösbar verbindbaren Elemente im verbundenen Zustand auszuüben.

2. Artikel nach Anspruch 1, bei dem das erste lösbar verbindbare Element eine Vielzahl von Hakenelementen aufweist und das zweite lösbar verbindbare Element eine Vielzahl von Ösenelementen aufweist.

3. Artikel nach Anspruch 1, bei dem das erste lösbar verbindbare Element eine Vielzahl von Ösenelementen aufweist und das zweite lösbar verbindbare Element eine Vielzahl von Hakenelementen aufweist.

4. Artikel nach einem der Ansprüche 1 bis 3, bei dem das zweite lösbar verbindbare Element (22) intermittierend mit dem vorderen Endabschnitt (16) verbunden ist oder das erste lösbar verbindbare Element (40) intermittierend mit dem hinteren Endabschnitt (17) an einer Vielzahl von voneinander beabstandeten Verbindungslinien (32) verbunden ist.

5. Artikel nach Anspruch 4, bei dem die Verbindungslinien (32) Klebstofflinien sind.

6. Artikel nach Anspruch 4, bei dem die Verbindungslinien (32) mittels Schall erzeugte Verbindungslinien sind.

7. Artikel nach Anspruch 4, bei dem die Verbindungslinien (32) mittels Heißsiegeln erzeugte Verbindungslinien sind.

8. Artikel nach einem der Ansprüche 4 bis 7, bei dem jede Verbindungslinie (32) eine Breite von etwa 1 mm bis etwa 15 mm aufweist.

9. Artikel nach einem der Ansprüche 4 bis 8, bei dem die Verbindungslinien (32) in einem Abstand von etwa 1 mm bis etwa 30 mm voneinander beabstandet sind.

10. Artikel nach einem der Ansprüche 2 bis 9, bei dem die Vielzahl von Haken in eine einzige Richtung ausgerichtet ist.

11. Artikel nach einem der Ansprüche 2 bis 9, bei dem die Vielzahl von Haken unterschiedlich ausgerichtet ist.

12. Artikel nach einem der Ansprüche 2 bis 11, bei dem die Vielzahl von Haken eine Hakendichte im Bereich von etwa 30 Haken/cm² bis etwa 160 Haken/cm² aufweist.

13. Artikel nach einem der Ansprüche 2 bis 12, bei dem die Vielzahl von Haken im allgemeinen in Reihen angeordnet ist mit einer Reihendichte im Bereich von etwa 3 Reihen/Linearzentimeter bis etwa 30 Reihen/Linearzentimeter.

14. Artikel nach einem der vorhergehenden Ansprüche, bei dem eine Spannung zwischen 19,69 g/cm (50 g/lb) bis 196,99 g/cm (500 g/lb) zwischen dem ersten lösbar verbindbaren Element (40) und dem zweiten lösbar verbindbaren Element (22) im verbundenen Zustand ausgeübt wird.

15. Artikel nach einem der vorhergehenden Ansprüche, bei dem eines der lösbar verbindbaren Elemente einen ortsfesten Basisabschnitt (60) und einen frei beweglichen Klappenabschnitt (62) aufweist und das andere lösbar verbindbare Element lösbar verbindbar zwischen dem ortsfesten Basisabschnitt (60) und dem frei beweglichen Klappenabschnitt (62) ausgebildet ist.

16. Artikel nach Anspruch 15, bei dem das andere verbindbare Element ein dehnbares Material aufweist.

Revendications

1. Article absorbant (2), comprenant :

un composite comprenant un substrat et un absorbant (8) sur ledit substrat, ledit composite comprenant en outre des portions d'extrémité avant (16) et arrière (17) disposées à l'opposé l'une de l'autre, un premier élément (40), susceptible de venir en prise libérable, positionné sur ladite portion d'extrémité arrière (17) dudit composite, un second élément (22), susceptible de venir en prise libérable, associé à ladite portion d'extrémité avant (16) dudit composite, lesdits premier (40) et second (22) éléments

susceptibles de venir en prise libérable étant susceptibles de venir en prise mutuelle libérable au moyen d'un système à boucles et crochets,





ledit article absorbant étant caractérisé en ce que :



ledit premier (40) et ledit second (22) éléments susceptibles de venir en prise libérable sont montés élastiquement par rapport audit composite pour qu'une tension prédéterminée soit appliquée auxdits éléments susceptibles de venir en prise libérable lorsqu'ils sont en prise.

2. Article selon la revendication 1, dans lequel ledit premier élément susceptible de venir en prise libérable comprend une pluralité d'éléments formant crochets et ledit second élément susceptible de venir en prise libérable comprend une pluralité d'éléments formant boucles.
3. Article selon la revendication 1, dans lequel ledit premier élément susceptible de venir en prise libérable comprend une pluralité d'éléments formant boucles et ledit second élément susceptible de venir en prise libérable comprend une pluralité d'éléments formant crochets.
4. Article selon l'une des revendications 1 à 3, dans lequel ledit second élément susceptible de venir en prise libérable (22) est réuni par intermittence à ladite portion d'extrémité avant (16) ou ledit premier élément susceptible de venir en prise libérable (40) est réuni par intermittence à ladite portion d'extrémité arrière (17) au niveau d'une pluralité de lignes de réunion (32) écartées les unes des autres.
5. Article selon la revendication 4, dans lequel lesdites lignes de réunion (32) sont des lignes d'adhésif.
6. Article selon la revendication 4, dans lequel lesdites lignes de réunion (32) sont des lignes de liaison par ultrasons.
7. Article selon la revendication 4, dans lequel lesdites lignes de réunion (32) sont des lignes de scellement thermique.
8. Article selon l'une des revendications 4 à 7, dans lequel chacune desdites lignes de réunion (32) a une largeur comprise entre environ 1 mm et environ 15 mm.
9. Article selon l'une des revendications 4 à 8, dans lequel lesdites lignes de réunion (32) sont espacées les unes des autres d'environ 1 mm à environ 30 mm.
10. Article selon l'une des revendications 2 à 9, dans lequel ladite pluralité de crochets est orientée selon

une direction unique.

11. Article selon l'une des revendications 2 à 9, dans lequel ladite pluralité de crochets a des orientations multiples.
12. Article selon l'une des revendications 2 à 11, dans lequel ladite pluralité de crochets a une densité de crochets comprise dans la gamme allant d'environ 30 crochets/cm² à environ 160 crochets/cm².
13. Article selon l'une des revendications 2 à 12, dans lequel ladite pluralité de crochets est généralement disposée en rangées et a une densité de rangées comprise entre environ 3 rangées par centimètre linéaire et environ 30 rangées par centimètre linéaire.
14. Article selon l'une des revendications précédentes, dans lequel une tension comprise entre 19,69 g/cm (50 g/pouce) et 196,99 g/cm (500 g/pouce) est appliquée entre ledit premier (40) et ledit second (22) éléments susceptibles de venir en prise libérable lorsqu'ils sont en prise.
15. Article selon l'une quelconque des revendications précédentes, dans lequel l'un desdits éléments susceptibles de venir en prise libérable comprend un panneau de base fixe (60) et un panneau formant volet librement mobile (62), et en ce que ledit autre élément susceptible de venir en prise libérable est susceptible de venir en prise libérable entre ledit panneau de base fixe (60) et ledit panneau formant volet librement mobile (62).
16. Article selon la revendication 15, dans lequel ledit autre élément susceptible de venir en prise est constitué d'un matériau extensible.








FIG. 7




FIG. 8




FIG. 9




FIG. 10




FIG. 11




FIG. 12




FIG. 13A

FIG. 13B




FIG. 14





FIG. 15



THIS PAGE BLANK (USPTO)